HP Latex 1500 Printer



Produce superwide 3.2 m (126 in) applications with speed, quality, and control



Fast, productive superwide applications

- Print SAV at 45 m² (480 ft²)/hr indoor quality¹, PVC banner at 74 m² (800 ft²)/hr outdoor quality.²
- Deliver vivid textiles quickly up to 24 m² (260 ft²)/hr³; optional ink collector kit for porous textiles.4
- Automatically print double-sided backlit applications with the optional double-sided day night kit.5
- Cut risk, eliminate delays prints are dry and scratch resistant⁶ immediately after printing.

Quality results - with every print

- Get the colour and quality you expect with innovative HP technology including OMAS, embedded spectrophotometer.
- Match tile edges confidently advanced features enable HP printheads to deliver colour consistency <=2 dE2000.
- Maintain quality print after print with 1200 dpi HP Thermal Inkjet printheads and auto nozzle replacement.
- Get quality results over the life of the printer with timely, routine HP Print Care preventive maintenance.

Cut costs, keep control

- Help reduce your running costs with costeffective 5-liter HP ink cartridges.
- Do quick visual checks the accessible print zone features LED lighting.
- At-a-glance monitoring on a busy production floor with internal print server alerts and status beacon signals.
- More unattended printing a robust roll-to-roll design drives up to 150 m² (1600 ft²) PVC banner production.

For more information, please visit http://www.hp.com/go/latex1500

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at https://hplatexknowledgecenter.com/

At 6-pass, 6-colour, 100%. 45 m² (480 ft²)/hr requires the optional HP Latex 1500 Dual Roll Kit. At 3-pass, 6-colour, 90%. At 12-pass, 6-colour, 170%.

⁴ The HP Latex 1500 Ink Collector Kit is an optional accessory for printing on porous textiles and mesh banner. To be available after the introduction of the HP Latex 1500 Printer.

⁵ Printing double-sided backlit applications requires the optional HP Latex 1500 Double-sided Day Night Kit. Front-to-back image registration accuracy of 2 mm or better when using certified PVC banner and paper media,

see http://www.hp.com/go/mediasolutionslocator.

6 Scratch resistance is comparable to hard-solvent inks on self-adhesive vinyl and PVC banner. Scratch-resistance comparison based on testing third-generation HP Latex Inks and representative hard-solvent inks.

Estimates by HP Image Permanence Lab on a range of media.

⁷ The colour variation inside a printed job has been measured to be within this limit: maximum colour difference (95% of colours) <= 2 dE2000. Reflective measurements on a 943 colour target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. 5% of colours may experience variations above 2 dE2000. Backlit substrates measured in transmission mode may vield different results

Technical specifications

Print

Printing modes	16 m²/hr (170 ft²/hr) - High Saturation Backlits (18-pass 6-colour 260%) 24 m²/hr (260 ft²/hr) - Textiles and Canvas (12-pass 6-colour 170%) 45 m²/hr (480 ft²/hr) - Indoor High Quality (6-pass 6-colour 100% / 6-pass 6-colour 120%) 57 m²/hr (610 ft²/hr) - Outdoor Plus (4-pass 6-colour 100%) 74 m²/hr (800 ft²/hr) - Outdoor (3-pass 6-colour 90%)
Print resolution	Up to 1200 x 1200 dpi
Ink types	Water-based HP Latex Inks
Ink cartridges	7 (black, cyan, light cyan, light magenta, magenta, yellow, HP Latex Optimiser)
Cartridge size	5L
Printheads	4 (cyan/black, magenta/yellow, light cyan/light magenta, HP Latex Optimiser)
Long-term print-to-print repeatability	Maximum colour difference (95% of colours) $\le 2 \ dE2000^1$
Media	
Handling	Roll-to-roll, double-sided blockout, dual-roll (optional), roll-to-freefall (optional), double-sided backlit (optional), ink collector (optional)
Media types	$Banners, self-adhesive\ vinyls,\ films,\ papers,\ wall coverings,\ canvas,\ synthetics,\ fabrics,\ mesh,\ textiles^2$
Roll size	Up to 3.2 m (single roll); Up to 2 x 1.6 m (optional dual roll)
Roll weight	Up to 160 kg (single roll); Up to 2×70 kg (with optional dual roll kit)
Roll diameter	30 cm
Thickness	Up to 0.4 mm (default); Up to 2.0 mm (with custom carriage height setting)
Applications	Vehicle graphics; Banners; Displays; Indoor posters; POP/POS; Exhibition and event graphics; Exterior signage; Light boxes - film; Textile
Connectivity	
Interfaces	Gigabit Ethernet (1000Base-T)
Dimensions (w x d :	xh)
Printer	574 x 138 x 167 cm
Shipping	586 x 181 x 191 cm
Weight	
Printer	1220 kg
Shipping	2000 kg
What's in the box	HP Latex 1500 Printer; HP 881 Latex Printheads; HP 871 Latex Printhead Cleaning Kit; 126-in spindles (x2); HP Internal Print Server; Documentation software; User manual; Media edge holders (x4); Original HP sample media; Cleaning supplies; Pneumatic gun
Environmental rang	ges
Operating temperature	15 to 30°C
Operating humidity	20 to 70% RH (non-condensing)
Acoustics	
Sound pressure	<70 dB(A) (operating), <57 dB(A) (idle)
Sound power	8.7 B(A) (operating), 7.3 B(A) (idle)
Power	
Consumption	8 kW (typical) - high-quality indoor mode (6-pass), 10 kW (typical) - outdoor mode (3-pass)
Certification	
Safety	IEC 60950-1+A1+A2 compliant; EU (LVD and MD compliant, EN60950-1, EN12100-1, EN60204-1, and EN1010); Russia, Belarus and Kazakhstan (EAC)
Electromagnetic	Compliant with Class A requirements, including: EU (EMC Directive)
Environmental	WEEE; EU RoHS; REACH; CE marking compliant

Ordering information

HD Latov 1500 Printo

Product

N4100H	THE LOLEX 1300 PTIME!	
Accessories		
D9Z41B M2J33A P4P91A P4P92A T0F91A T0F92A T4E58B	HP Large Format Onyx Thrive RIP Software HP Latex In-line Slitters HP Latex 1500 Double-sided Day Night Kit HP Latex 1500 Ink Collector Kit HP Latex 1500 Dual Roll Kit HP Latex 1500 K Collector Foams Kit HP Latex Media Saver Kit	
V8A82A W3U61A	HP Latex 1500 Edge Holder Kit HP Latex 1500 Roll-to-freefall Kit	

Original HP printing supplies

CR327A	HP 881 Yellow/Magenta Latex Printhead	
CR328A	HP 881 Cvan/Black Latex Printhead	
CR329A	HP 881 Light Magenta/Light Cyan Latex Printhead	
CR330A	HP 881 Latex Optimizer Printhead	
CR331A	HP 881 5-liter Cyan Latex Ink Cartridge	
CR332A	HP 881 5-liter Magenta Latex Ink Cartridge	
CR333A	HP 881 5-liter Yellow Latex Ink Cartridge	
CR334A	HP 881 5-liter Black Latex Ink Cartridge	
CR335A	HP 881 5-liter Light Cyan Latex Ink Cartridge	
CR336A	HP 881 5-liter Light Magenta Latex Ink Cartridge	
CR337A	HP 881 5-liter Latex Optimizer Cartridge	
G0Y99A	HP 871 Latex Printhead Cleaning Kit	

Original HP large format printing materials

HP Permanent Gloss Adhesive Vinyl (REACH certified³)

HP Backlit Polyester Film⁴ HP PVC-free Durable Smooth Wall Paper (REACH³, FSC^{®5}, UL GREENGUARD GOLD certified⁶) HP Premium Poster Paper⁴ (FSC[®] certified⁵)

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Service and Support

HA151AC HP Full Coverage Maintenance Support Contract HK965AC HP Shared Maintenance Hardware Support Contract nksosak nr Shalete Maintenance natuware Support Contract HK707AC HP Parts and Remote Hardware Support Contract W0R39A / K4T88-67259 HP Latex 1500 Printer Maintenance Kit K4T88-67260 HP Latex 1500 Service Maintenance Kit V8L81A / K4T88-67256 HP Latex 1500 Basic Uptime Kit

ECO highlights

- Better for printing companies/operators no special ventilation or HAPs
- Better for the end-customer, more differentiation odorless prints reach more indoor spaces?

 Better for the environment HP designs end-to-end sustainability into large-format printing.

 HP Latex Inks are UL GREENGUARD GOLD Certified³

Please recycle printing hardware and eligible printing supplies. Find out how at our website:

¹ Special ventilation equipment (air filtration) is not required to meet U.S. OSHA requirements. Special ¹ Special ventilation equipment (air filtration) is not required to meet U.S. OSHA requirements. Special ventilation equipment installation is at the discretion of the customer – see the Site Preparation Guide for details. Customers should consult state and local requirements and regulations. HP Latex Inks were tested for Hazardous Air Pollutants, as defined in the Clean Air Act, per U.S. Environmental Protection Agency Method 311 (testing conducted in 2013) and none were detected.
² There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.
³ UL GREENKUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL'S GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information with the Vieway und complion or http://www.nereporual.org.

information, visit http://www.ul.com/gg or http://www.greenguard.org.

1 Reflective measurements on a 943 colour target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard D5 014-6/E:2012. Backlit substrates measured in transmission mode may yield different results.

2 Performance may vary depending on media—for more information, see http://www.hp.com/go/mediasolutionslocator. For best results, use textiles that do not stretch. The optional ink collector is required for porous textiles.

3 This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at HP Printing Products and Consumable Supplies.

4 HP Large Format Media take-back program availability varies. Some recyclable HP papers can be recycled through commonly available recycling programs. Recycling programs may not exist in your area. See http://www.HPLFMedia.com/hp/ecosolutions for details.

5 BMG trademark license code FSC®-C115319, see http://www.fsc.org. Not all FSC®-certified products are available in all regions.

6 UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL'S GREENGUARD Standards for low chemical emissions into indoor air during product usage. For more information, visit http://www.ul.com/gg or http://www.greenguard.org.























